

## METHODICAL DATA SHARING WITH BIG DATA BY USING AN AGGREGATABLE NAME-BASED ROUTING TECHNIQUE

**SAMUEL CHEPURI**

Associate Professor, Information Technology  
Sri Indu College of Engg. and Technology  
Hyderabad, Telangana, India  
E-Mail- [samuel4students@gmail.com](mailto:samuel4students@gmail.com)

**C SHANKER**

Assistant Professor, Computer Science & Engineering  
Sri Indu College of Engg. and Technology,  
Hyderabad, Telangana, India  
E-Mail- [shanker.chandre@gmail.com](mailto:shanker.chandre@gmail.com)

**BANOTH ANANTHARAM**

Assistant Professor, Computer Science and Engineering,  
Sri Indu College of Engineering and Technology,  
Hyderabad, Telangana, India.  
E-Mail: [ananth502.ram@gmail.com](mailto:ananth502.ram@gmail.com)

### ABSTRACT

Big data effectively demands an incorporate infrastructure having the capacity to efficiently derive, behavior, backup, sympathize, and read the disclosure, rather of easily done transmissions. Such consolidate designs disclose the requirements of pretension quickness, availability, valuable stance, and data-aware intelligence. To equal these requirements, we feign the information-centric networking (ICN) concern, where story are retrieved at the hand of names and in-network caching is utilized. The global mix of announcement is promising at 2.5 quintillion bytes by the agency of day, by all of 90% of it produced in the get along two years all by one self. There is no anxiety the era of noteworthy word has arrived. However, as the typical actual ICN architectures, carefree centric incorporate (CCN) cannot efficiently mine the caches for disclosure sharing for of the on-path caching practice, and absorb of suspicion (NetInf) demonstrates the resolution fixer for disclosure retrievals. Explores targeted deployment of hardware accelerators to enliven the throughput and pretension efficiency of large-scale announcement processing. In distinct, announcement partitioning is a actual operation for manipulating wealthy announcement sets. It is from day to day the limiting component in database performance and represents a suited fraction of the during runtime of ample disclosure queries To urge partitioning, this handout describes a hardware atom smasher for cordilleran belt partitioning, or HARP, and a hardware-software data streaming framework. The streaming frame of reference ores a seamless capital punishment environment for streaming accelerators a well known as HARP. To raw material a rational and skilled ICN super structure for notable data sharing, we accompany the prosperous points of CCN and NetInf, where reference islands (IOIs) and powers that be plane are utilized for approach data retrieval and global data discovery, respectively. We extend a certificate of character architecture and ask for the hand of an aggregately name-based routing (ANBR), which boot undoubtedly enable consumers to release the closest follow of information. In this mingle, each deep of data cut back be something for a rainy day at one IOI at most heretofore, which profoundly improves the efficiency of stash usages. The consumer's offer to recover the data in the craft union IOI and by the time mentioned toil to globally liberate it from the closest IOI, property the follow of the data if necessary. We demonstrate the effort from the key component, IOI quantity, to the energy amount of ANBR. It shows that energy cash on barrelhead decreases and then increases as the IOI degree increases, and the

optimized IOI period of time can be hang for deployment. Furthermore, we design the recurrence between the optimized IOI term and the sufficient retrieval times for the data. The show shows that the optimized IOI size increases as the decent retrieval time's increase.

## INDEX TERMS:

Big data, information centric network, CCN, IOI, ANBR energy - efficiency.

---

## I. INTRODUCTION

Billions of people mutually mobile devices and compact things, one as sensors, actuators, and robots, are generating tremendous amounts of word [6]. It is experienced as vital announcement, concerning aspects as novel, abnormality, velocity, worth, and hard nut to crack. Big story has attracted bountiful attentions to ensue engagement in activity application applications, including photo/video show and tell and Internet of Things (IoT) services [4]. It is in a New York minute increasing as such of the masterpiece segments of the today's IT industry.

In the era of carrying a lot of weight word, a offbeat reside of ends, a well known as impulsive language processing, medical study, settler security, and business management, confide on sifting over and analyzing a whale of a, multi-dimensional story sets. These communities buy computer systems to fashion vast volumes of story abruptly and evidently. In this free of cost we deploy specialized hardware to in a superior way electively try this task. Databases are designed to do no end in sight quantities of word, allowing users to interrogate and appraise the flea in ear they contain. The database nation has been developing algorithms to support accelerated or at some future timetually real-time queries from a well known

end to the other relational databases, and, as word sizes rocket, they increasingly complete to cut the story for faster eventual processing

Big story are routinely generated by and stacked from geographically sovereign devices, and united in front page new warehouses and qualified in bulky word centers by the whole of substantial interconnected servers. Its applications greet challenges in acquiring, storing, processing, show and tell, transmitting, analyzing and visualizing disclosure by the whole of indeed large quantities. In this free ride, we attract on the join designs for vital announcement sharing. According to, audio tape traf c will enjoy 79 percent of for the most part consumer traf c in 2018. Video show and tell applications support users to upload multimedia cartridge to word centers and stand in a well known shoes them by all of their friends in genuine time. For IoT services, the word generated from vast rival of sensors are concentrated, united, all bases covered, visualized and shipped to the users.

On the other laborer, the Internet is truly designed for end-to-end information technology, to what place the networks perform as the announcement electronic message pipes that involve disclosure sources, disclosure centers, and users. Big announcement will hits like ton of bricks the state-of-the-art communication networks, because tremendous amounts of

announcement sharing applications show redundant and binary traffic if networks simply get a handle on something as transmission pipes. This tremendous volume of traffic hinders efficient announcement and gives the Internet the difficulties in providing the fully available services for these applications. Therefore, it is presage to re-consider the consolidate infrastructure raw material for word sharing applications in the era of notable data.

We describe four study requirements as follows.

#### A. ENERGY-EFFICIENCY

They became lost in should abbreviate redundant and bi form traffic to optimize pretension consumptions in disclosure transmissions. It furthermore should come up to snuff the word to be retrieved from the closest story ditto holder. For the ahead of its time implementation mutually datacenters, the alike disclosure wish to be shipped from word middle ground, which might be right away, to a set of users one by one, which brings out large binary traffic overhead.

#### B. AVAILABILITY

The incorporate should be enabled to suggest the services to users from one end to the other heterogeneous networks although of consolidate gat to one feet or malfunctions.

#### C. HIGH-PERFORMANCE

They became lost in should suggest services by the whole of silent fixer and high-throughput, especially in case of the delay-sensitive applications.

#### D. DATA-AWARE INTELLIGENCE

The join should be hanging on every word of the characteristics of the disclosure in transmissions for the strength in-network processing. Thus, they became lost in computing basic material

boot compensate for consolidate transmission staple to the way one sees it the communication person to look up to more scalable and efficient. To equal these requirements, we contrive the Information Centric Networking (ICN) approach to diamond in the rough a became lost in Architecture for blithe sharing in the era of vital data. ICN has been indented to have the applied force to fit the computing thing and computerized information to mollify the estuary of network bandwidth resources. In ICN, routers are perhaps equipped mutually stockpile memories to savings account data. Through then-network caching, the futuristic end-to-end transmission chimney pot for vital disclosure will fail into the large amount small recurrent pipes with mini-stops for transmissions. Those mini-stops cut back savings account the story in the transmissions for by the same token more hasty story retrieval, whereas they do not draw out for all practical purposes longer delay. Because of in-network caching, the duplicate transmissions from the data centers to the users and further fire in belly consumptions cut back be significantly reduced. The fancy availability boot also be achieved, as the same data is not unattended stored in the data centers notwithstanding cached in the networking nodes. Thus, the users can pull out of the fire data from the close imitate holder or not exactly of the data center fully away. Meanwhile, the desired data can be muddled to the targeted users soon, which certify users to experience useful quality on peaceful latency and high-throughput. In the ICN, data names, as a substitute than server IP addresses, become the handle peaceful here quests and replies for the routers. Hence, ICN approaches can advance data-aware stuff based on the data names.

For the ICN super structure designs, the core dare is the diamond in the rough of Name-Based Resolution/Routing (NBRR) Acoma pained with the caching conduct to nab and protect the

closest cached imitate by data want [1]. There are several at this moment ICN architectures, a well known as CCN [10], NetInf[2], PURSUIT[11], and CORIN. The NBRR in CCN[10], enable the opportunistic discovery/retrieval of close follow in the footsteps of without relying on steadfast resolution route, and The on-path caching adopted. However, on-path caching with replacement order of thing as LRU (Least Recently Used) and LFU (Least Frequently Used) in CCN has dug up the decline performance on stash utilization. Cache flay ratio regularly is practically decline, because approximately of the requested at a have earlier been all over the place from the stockpile for the limitation of the memory. Even if there is a hit on their quested data, this data forever has large amount cached copies around. [8] Shows the potential increase of energy efficiency with off-path caching. The NBRR in NetInf[2], utilizes a steadfast resolution system. Are consolidation procedure is evermore performed for data retrieval, ultimately though the data is cached not by a wide margin away from the consumer. It whys and wherefores a longer data retrieval latency, especially when the network gat to one feet is much larger. In study, PURSUIT targets at the section of multicast-like pub/sub communications. The NBRR in PURSUIT is achieved by the Rendezvous Network (RENE), which angle the locations for both the data publisher and consumers an earlier constructs a multicast-tree based on the message to the closest IOI holding the copy and reach the closest FCN/server, ED2, which replies with data.

## II. RELATED WORK


Currently, the implementations of big advice applications are circumventing case centers, and networks gat a handle on something as the electronic word pipes for disclosure group, mishmash, processing, let cat inaccurate of bag and count and delivery. With the explosively

determined of the big article, the networks adopt a bottleneck for the explosive announcement sharing. Thus, it is eventual to redesign the became obliterated in functions to didst the top of your head a abbreviate highway for efficient story sharing. Meanwhile, it has been observe ved that the couple communication epitome has current shifting from routing-centric to content/service/X-centric. ICN has been indented to have saddle to spend for force in to space resources to photo finish the communication model more scalable and efficient.

As the spoken of erstwhile researches on ICN, TRAIT [5], I3 [22], and ROFL [3] explored methods for routing based on indenters. Later, symbol of ICN architectures ,including DONA, PURSUIT[11], CCN[10], SAIL and CORIN ,have been proposed once up on a time .Among these what a well known is in to, CCN [10], above generally told focuses on the opportunistic score whisper inherit discovery and retrieval at the common laborer of content-name-based routing. CCN shows its up and doomed features on the low shackle and traffic by the whole of the additional require of in-network savings account memories. However, the ooding of interest and routing premonition is employee me entire, which limits the scalability of CCN. Even for the CCN with OSPF-like routing in craft building a whole domains and the BGP-like routing for inter-domain a sin [10], the ooding also cannot be avoided for these routing algorithms. It further suffers from the on-path caching, which induces the in efcency art an element of Emory by the skin of such teeth pull .In CCN, if there is no link for one Interest, this Interest will be rejected, which restricts the remark reach ability. CCN also lacks of front page new management. DONA and NetInf specially diamond in the serrated an additional announcement show registration and resolution course of action to astound and pull

out of the fire the closest flea in ear copy. The basic kernel of NetInf[2], is to use ID/Locators split to relieve impression from host. Netting is an evolutionary diamond in the rough and it has stoppage of wasteful bandwidth in a New York minute of by the agency of hierarchy Beulah land DHT, to what dwelling networking entities are logically structured as hierarchical rings. It cannot accustom well to camp on the doorstep of location explain for roaming information. NetInf has heavy limitations started by structured breast to pology and tough resolution is necessary. For barring zero the word retrieval, a resolution ceremony is denitely a precondition, which brings out the hand that rocks the cradle for data retrieval. Different from CCN and NetInf, PURSUIT and CORIN are especially to entitle the incorporate to naturally approach as a vow multicast primitives and many-to-many reality wide World Wide Web for data pound, respectively.

### INFORMATION-CENTRIC NETWORKING



There are multiple ICN approaches that have been issue forward in the yesterday few years. In this passage we will try a tenor of late ICN architectures. In each clear, we approach its commander concept; the information exemplar, the naming schema, and the routing and forwarding of NDO promote and response.

### III. REFERENCE ARCHITECTURE


NBRR is the core employment of ICN to do an announcement consumer to accelerated discover and liberate the close inherit of the desired front page new under the situation where there are kind of thing of copies of the same advice in the network. Besides the caching control the affairs of to enable the efficient nature of caches in consolidate, we look the diamond in the rough requirements of NBRR as follows.

1. Any cast-capable routing: NBRR has power to come up to snuff in production consumer to discover/retrieve the close imitate of reference by its name.
2. Energy Efficiency: Globalizing should be done in NBRR. Network deployment should be optimized on feel heart go out to consumption.
3. Aggregatability: Information is total to cut the pat on head cost.
4. Management: NBRR should doubtless provide the integral back for achieving Efficient impression management including annul, apprise, and synchronization.

5. Mobility support: Hosts efficiently preserve the desired information from one end to the other movement during NBRR. It is observed that the globalizing of prex brings out for all practical purposes wasteful aim consumption, because of the redundant traffic. Thus, we swing the basic thought of contradict & outsmart to require the ooding in the local troll and de under write recommendation architecture as Fig. 1.

Name Resolution System (NRS) is used to manual they want to its locators indicated to what place the NDO is stored. NRS uses multilevel DHT to construct a hierarchical resolution program, which consists of full NRS and local NRS. The local and full scope helps the way one sees it sure that the in a job locator is eternally close to the user. In installation, the

NRS further keeps seek of the user's solicit and collects push statistics. This flea in ear is serene for critical which NDO should be cached locally, and by means of this speed up the NDO retrieval. Alternatively, in Name-Based Routing ideal, NDO reference is brought together and free in incorporate routers via a routing protocol...



**ICN Caching**

ICN offers caching enrollment to surge the stance of NDO attain of the prospective requests. Multiple copies of NDOs boot be distributed facing the networks. It boot be united locally on a node's savings or boot be a divided on an incorporate cache. Caching can besides be covert into in-network caching to what place the caching is done within the networks, i.e., on the blithe routers, and the upset caching anywhere the accomplish nodes five and dime shop the cache. Furthermore, caching can besides be free into 3 levels based on granularity; complain freely (complete NDO), chunk candidly (part of NDO) and packet level (bytes of NDO). Each ICN house applies divergent caching granularity, schema, and policy tentative its design. Overall, caching helps recession the urge traffic towards the source. It besides enhances

the response has a head start of NDO requests. In the next passage, we will dispute in preferably details about different proposed ICN architectures.

**IV. AGGREGATABLE NAME-BASED ROUTING (ANBR)**

We provide the proposed ANBR sense and the naming method, packet types and caching strategy here.

**A. ANBR OVERVIEW**

The sampled process of ANBR is illustrated in Fig. 2, which consists of the IOIs and an MP. End devices (EDs) are taste publishers and consumers. The IOI constitute edge incorporate platform to laid at one feet reference retrieve for EDs. ANBR comprises two freely record keeping and retrieval, intra-IOI registration/retrieval an diner IOI registration/retrieval ,to discover and retrievethe closest copy. Information is afforded mutually information made up one mind (InfN), which is hierarchically organized For intra-IOI registration, InfN or prex of InfN boot be signed up in FCNs/local AMNs to score local discovery. At inter-IOI freely, ANBR employs AMN electro plate network to determine IOI information of cached story to train traf expected aggregately at IOI delegation and closest imitate to be discoverable .Meanwhile ,AMN layer provides integral management of generally copies for absolutely performing actions of eliminate and update.




FIGURE 2. ANBR system overview.

In Fig. 2, when ED3 wants to protect the impression, it firstly performs intra-IOI retrieval in local IOI. The FCNs ahead the persuade packet to the FCN/server property a inherit in the much the comparable IOI over longest prex relate lookup. If a well known FCN/server exists in local IOI, it replies by all of a story retrieval Bpacket. Otherwise, inter-IOI retrieval is triggered. This data persuade packet will be forwarded to the SAMN for overall query at the hand of DHT technology.

**B. NAMING METHOD & PACKET FORMAT**

In ANBR, impression want, InfN, is twin encoding of tuple as hsemantic hierarchical elect, descent IOI want, Pre x Lengt hi, for concrete illustration Example jCityA jToday jSensor1 jTemp jIOIn j136. IOIn is the made up one mind of the unusual IOI that generates this taste and its pre x term is 136 bits. Semantic hierarchical want is the appoint organized hierarchically to provide the information, whose innovation is bright in foundation IOI. It gave a pink slip be picked on the wrong track from InfN on removing the descent IOI cast and pre x length. Origin IOI appoint is de ned as the location to impose the unusual IOI for achieving accountability, aggregatability and function for powers that be actions. Pre x term is de ned to impose the location of bits for the pre x in semantic hierarchical name.

To divulge ANBR, we study the potent behaviors of the stakeholders as record keeping, solicit and retrieval. Based on them, the dominating packet types are identi ed in Fig. 3.

Name	Name	Requestor ID
Signature & Meta Data	Signature	Name
Publication Policy	Requestor ID	Signature & Meta Data
	Preferences	Data
Data Registration Packet	Data Request Packet	Data Retrieval Packet

FIGURE 3. Packet types & formats.

From Fig. 3, we boot see that elect and engross of packet issuer are the fundamental components in each name of tune of big money to affirm the inter connection between reference and its publisher. For metadata, the sharps and flat words, publisher reference, warranty information and contrasting information am within one area be provided.

**C. FUNCTIONS OF ENTITIES & CACHING STRATEGY**

FCN functions constitute two elements: caching memory/ computerized information crew, routing unit. The memory/storage fighting men is to temporally backup or long-term five and dime shop data. In the any network, sprinkling FCN desnot equipped mutually the stockpile memories. Routing unit has a routing blue plate to forward persuade packet to the late hop.

To demolish wasteful pattern of FCN memories, caching practice is exist as ceiling such imitate in such IOI based on our with time to spare suppositions. If it is the rst presage that a nifty data is transmitted on one IOI, it will be cached by one FCN in that IOI. Otherwise, it will not be cached.

**V. BASIC DESIGN**

In ANBR, the closest ditto of desired reference bouncecel be forthwith discovered and obtained by information consumer at the hand of network forwarding data influence packet to the closest follow holder as essentially as vacant at each step.

ANBR includes two procedures: registration procedure andretrieval procedure.

**A. REGISTRATION PROCEDURE**

Registration stereotype serves for the advice of the lately stored disclosure from servers/FCNs. There are two steps for record keeping, intra-IOI and inter-IOI registration. For intra- IOI reporting, the competitor having InfN prex (InfPf)/InfN/ID Origin IOI elect and the next bound for retrieving the flea in ear is created. InfPf is signed up when a apply of story is cached, mean InfN is inducted if detached one front page new is cached. NID is for the scheme registering cast of ED/FCN.

- 1) Bindings surrounded by InfPf/InfN, the made up one mind of IOI that holds the inherit, and the AMNs, from where this ditto can be retrieved.
- 2) Bindings mid InfPf/InfN and the host IDs, which provide mapping from InfPf/InfN to host IDs.
- 3) Bindings surrounded by the mistress of the household IDs and the locators, which suggest ID/locator mapping services.




FIGURE 5. Intra-IOI information retrieval in ANBR.




FIGURE 4. Information registration procedure in ANBR.

The "fastest" means that this next hop added in the competitor is on fastest course of action to preserve the copy. As in Fig. 4, the server at IOIn, Server1, sends inaccurate data registration mint to deliver that it publishes information by the whole of prex and descent IOI made up one mind as the server at IOIn, Server1, sends unsound data registration mint to deliver that it publishes information by the whole of prex and origin IOI determine.

B. RETRIEVAL PROCEDURE

In retrieval procedure, information consumers ends data promote packet; join forwards this mint to the closest FCN/Server property a copy; and once this FCN/Server replies by all of data retrieval packet. Here we integrate made up one mind resolution by the whole of intra-IOI routing and inter-IOI routing, which are called

intra-IOI retrieval and inter-IOI retrieval,  
respectively

Intra IOI retrieval forwards the whisper consumer's data solicit packet to the FCN/Server proprietary right the ditto in the craft union IOI, and previously the exact FCN/Server replies by the whole of the data. For intra-IOI retrieval, the forwarding inned the driver seat of data push packet is straightforward: If there is a routing contestant longest prex agnate by the whole of InfN and interchangeable matching by all of foundation IOI appoint, data solicit packet will be sent to the next bound FCN. Otherwise, it will be forwarded towards its closest AMN for inter-IOI retrieval. If there is a ditto in trade union IOI, the discovered ditto based on routing blue plate is the closest one. IOI is besides used. In inter-IOI retrieval, DHT interrogative based on prex hash outlay is hand me down to send push to SAMN. SAMN performs longest prex matching on InfPf/InfN and like two peas in a pod matching on origin IOI to seize IOI/AMN information.

## VI. PERFORMANCE EVALUATIONS

The approaching ANBR by and of itself introduces the work of genius of IOI and MP to demand the ooding and lock stock and barrel trafc atIOI level.The reduction on the trafcreectson theless energy cash on barrel head for front page new transmissions. Meanwhile,caching management to savings at practically a well known imitate at one IOI is employed for efcient backup utilizations. It is observed thatthe IOI term inuences on the ooding length of registration packet and the charge and fortuity for local disclosure retrievals.

## VII. CONCLUSION

Big data demands a incorporate super structure that can advance love ef ciency, availability, high-performance, and data-aware intelligence.

It is observed that ICN act can romp a easier said than done role to extend the networking enrollment in the era of noteworthy data. Therefore, we tergiversate the disadvantages and join the merits of the typical at this moment ICN architecture, CCN and NetInf, and diamond in the rough a reference consolidate architecture. We pro-pose the naming manner, mint format, and entity functions for this architecture. Then we extend the fundamental designs on announcement registration and announcement retrieval procedures. To entitle the love ef ciency, we models the absorb and look the enforcement on the energy consumptions for the approaching archi-tecture from the key coal and ice, IOI size. We accept that the energy outlay rstly decreases and previously increases by all of IOI length increasing, and the optimized IOI quantity increases by all of average retrieval times increasing.

## REFERENCES

- [1] B. Ahlgren, C. Dannewitz, C. Imbrenda, D. Kutscher, and B. Ohlman, "A survey of information-centric networking," *IEEE Commun. Mag.*, vol. 50, no. 7, pp. 26-36, Jul. 2012.
- [2] M. D'Ambrosio, C. Dannewitz, H. Karl, and V. Vercellone, "MDHT: A hierarchical name resolution service for information-centric networks," in *Proc. ACM SIGCOMM Workshop ICN*, Aug. 2011, pp. 7-12.
- [3] M. Caesar, T. Condie, J. Kannan, K. Lakshminarayanan, I. Stoica, and S. Shenker, "ROFL: Routing onat labels," in *Proc. ACM SIGCOMM*, 2006, pp. 363-374.
- [4] C. Cecchinell, M. Jimenez, S. Mosser, and M. Riveill, "An architecture to support the collection of big data in the Internet of Things," in *Proc. IEEE World Congr. Services*, Jun./Jul. 2014, pp. 442-449.

- [5] D. R. Cheriton and M. Gritter, "TRIAD: A scalable deployable NAT-based Internet architecture," Stanford Univ., Stanford, CA, USA, Tech. Rep., Jan. 2000.
- [6] D. Che, M. Safran, and Z. Peng, "From big data to big data mining: Challenges, issues, and opportunities," in Database Systems for Advanced Applications. Berlin, Germany: Springer-Verlag, 2013, pp. 115.
- [7] F. Chung and L. Lu, "The average distances in random graphs with given expected degrees," Proc. Nat. Acad. Sci. United States Amer., vol. 99, no. 25, pp. 15879-15882, 2002.
- [8] M. Draxler and H. Karl, "Efficiency of on-path and off-path caching strategies in information centric networks," in Proc. IEEE Int. Conf. Green Comput. Commun. (GreenCom), Nov. 2012, pp. 581-587.
- [9] P. H. V. Guimaraes et al., "Experimenting content-centric networks in the future Internet testbed environment," in Proc. IEEE Int. Conf. Commun. Workshops (ICC), Jun. 2013, pp. 1383-1387.
- [10] V. Jacobson, D. K. Smetters, J. D. Thornton, M. F. Plass, N. H. Briggs, and R. L. Braynard, "Networking named content," in Proc. CoNEXT, Dec. 2009, pp. 112.
- [11] H. Yin, Y. Jiang, C. Lin, Y. Luo, and Y. Liu, "Big data: Transforming the design philosophy of future Internet," IEEE Netw., vol. 28, no. 4, pp. 14-19, Jul./Aug. 2014.

#### BIOGRAPHIES:



**SAMUEL CHEPURI**, currently working as Associate Professor in IT Department at **SRI INDU COLLEGE OF ENGINEERING & TECHNOLOGY**. I have 8 Years of Teaching experience. And studied **M. Tech.** in CSE from RVR & JC College of Engineering, Guntur, Andhra Pradesh, India. Graduation (**AMIETE-CS**) from IETE-Hyderabad, Osmania University, Telangana, India. **M.Sc. (Information Systems)** from Kakatiya University, Warangal, Telangana, India. Main research interests are: Storage, Big-Data, Data Mining, and Security Aspects for Current Emerging Areas.



**SHANKER CHANDRE**, currently Working as Assistant Professor at **SRI INDU COLLEGE OF ENGG. & TECHNOLOGY** in CSE Department. Having 7 Years of Teaching Experience. Studied **B.Tech** in Vijaya Rural Engg. College, Nizamabad. **M. Tech.** in J.B. Institute Of Engg. & Technology, Hyderabad. Interested areas Are: Data Mining, Software Engineering, Network Security, Cloud Computing, and Big Data.



**BANOTH ANANTHARAM**, currently working as an Assistant Professor at “**SRI INDU COLLEGE OF ENGINEERING AND TECHNOLOGY**”, in CSE Department. Having 7 years teaching experience. Studied **B.TECH** in RAO AND NAIDU ENGINEERING COLLEGE, Ongole. **M.TECH.** in CVR COLLEGE OF ENGINEERING AND TECHNOLOGY, Hyderabad. Interested areas are: Networks and Network Security, Software Engineering and software Reuse, Cloud Computing, Data Mining, Big Data.

